

2017 Heli-Light FA-AV (PSA) Type One – Minimum Kit

FAA TSO - C70a, ETSO - 2C70a, CAA BCAR-B4-8 & DGAC QACI-144 Approved

Soft Pack Configuration with 406MHz ELT Installed



STANDARD EQUIPMENT Includes:

- CO₂/N₂ Inflation System w/ Twin Buoyancy Tubes
- **Three (3) Position (Closed, Sail, & Convertible) Light Weight Canopy**
- Sure-Seal Closures w/ #10 YKK Heavy Duty Zippering
- Dual Main Zipper w/ Ventilation Tie Backs
- **Single Arch, Auto Inflatable, Canopy Support System w/ Stay Erect Arch Support Valve System**
- Oversized Front Boarding Entry w/ 4 Rung Boarding Ladder
- Interior Assist Ladder w/ Quick-Release Fittings
- Rear Boarding Door w/ 3 Rung Boarding Ladder
- Four (4) Bowed Boarding Assist Handles
- Two (2) Bowed Boarding Stirrups
- Combination Foul Weather Observation Port Hole & Water Collection System w/ Sure-Seal Closures
- **Single Floor**
- Water Activated Interior/Exterior Survivor Locator Lights
- Quick-Grab Pelican Super MityLite Flashlight on Arch
- Auto-Deploying Hemispherical Drogue (Sea-Anchor) w/ 25' Line & Dual Anti-Foul Swivels
- 75' Floating Heaving Trailing Line w/ Buoyant Throwing Handle
- 35" Painter Line w/ Quick-Release Fittings
- Heavy Duty EZ Grip Righting Line with Contrasting Bowed Hand Grips
- Unidirectional Retro/Radar Reflective Segment across Arch
- Unidirectional Retro Reflective Segments under Life Raft & on Canopy
- **Pentagonal Ballast System (5 to eight person capacities only)**
- 1" Exterior Lifelines & Interior Grasp Lines
- Three (3) StoreSafe Light Weight Dry Survival Gear Storage Pockets
- Pressure Relief Valves
- **Topping-Up Valves**
- **UltimaWrap Vacuum Seal (3 yr. protection)**

Minimum SEP Kit Part 29/91/135 and EU OPS 1 Includes*:

- ① Manual Inflation Pump – Spring Loaded Return w/ Adapter
- ① Raft Knife
- ① USCG Aerial Meteor Flares
- ① Collapsible Bailer Bucket w/ Handle

JAR-OPS3 SEP Kit Includes 91/121/135 and EU OPS 1 Plus*:

- ② USCG Aerial Meteor Flares

Universal Minimum SEP Kit Includes Part 29/91/135 and EU OPS 1/3, JAR OPS 3 & CAR) Plus*:

- ① Repair Clamp (5")
- ② Sponges Compressed
- ① Signal Mirror
- ① USCG/SOLAS Whistle
- ① Sea-Dye Marker
- ① PUR Survivor "06" Watermaker
- ② Water Storage Bag
- ① Fishing Kit
- ① Survival Manual
- ① First Aid Kit
- ① Sea Sickness Tablets

ELT:

- Triple Frequency Survival (S) Type ELT, w/ Single Antenna (121.5/243.0/406MHz)
- TSO-C126, TSO-142, C/S T.001, JTSO-2C126



Call for details if ELT is not required.

Heli-Light FA-AV (PSA) Type One - Soft Pack (Minimum Kits) - With SRB 406MHz, Triple Frequency ELT

Winslow Model	SEP Equipment	Weight (LBS)	Pack Dimensions	Winslow Part Number
46FPSA Capacity 4 Overload Capacity 6	Part 91/135/EU OPS1 Minimum	31	7.5" x 19.5" x 20"	46FPSA-60M-1-110
	29 Minimum	30	7.5" x 19.5" x 20"	46FPSA-6M2-1-110
	JAR OPS 3 / EU OPS 3 Minimum	30	7.5" x 19.5" x 20"	46FPSA-63M-1-110
	CAR Minimum	34	7.5" x 19.5" x 20"	46FPSA-6CM-1-110
	Part 29/91/135/EU OPS1/3 & CAR Universal Min	35	7.5" x 19.5" x 20"	46FPSA-6UM-1-110
57FPSA Capacity 5 Overload Capacity 7	Part 91/135/EU OPS1 Minimum	34	8" x 16" x 20"	57FPSA-60M-1-104
	29 Minimum	33	8" x 16" x 20"	57FPSA-6M2-1-104
	JAR OPS 3 / EU OPS 3 Minimum	33	8" x 16" x 20"	57FPSA-63M-1-104
	CAR Minimum	37	8" x 16" x 20"	57FPSA-6CM-1-104
	Part 29/91/135/EU OPS1/3 & CAR Universal Min	38	8" x 16" x 20"	57FPSA-6UM-1-104
69FPSA Capacity 6 Overload Capacity 9	Part 91/135/EU OPS1 Minimum	36	8.5" x 18.75" x 19.25"	69FPSA-60M-1-115
	29 Minimum	35	8.5" x 18.75" x 19.25"	69FPSA-6M2-1-115
	JAR OPS 3 / EU OPS 3 Minimum	36	8.5" x 18.75" x 19.25"	69FPSA-63M-1-115
	CAR Minimum	39	8.5" x 18.75" x 19.25"	69FPSA-6CM-1-115
	Part 29/91/135/EU OPS1/3 & CAR Universal Min	40	8.5" x 18.75" x 19.25"	69FPSA-6UM-1-115
710FPSA Capacity 7 Overload Capacity 10	Part 91/135/EU OPS1 Minimum	38	9" x 12" x 25"	710FPSA-60M-1-106
	29 Minimum	37	9" x 12" x 25"	710FPSA-6M2-1-106
	JAR OPS 3 / EU OPS 3 Minimum	38	9" x 12" x 25"	710FPSA-63M-1-106
	CAR Minimum	41	9" x 12" x 25"	710FPSA-6CM-1-106
	Part 29/91/135/EU OPS1/3 & CAR Universal Min	42	9" x 12" x 25"	710FPSA-6UM-1-106
812FPSA Capacity 8 Overload Capacity 12	Part 91/135/EU OPS1 Minimum	41	9" x 12" x 25"	812FPSA-60M-1-102
	29 Minimum	41	9" x 12" x 25"	812FPSA-6M2-1-102
	JAR OPS 3 / EU OPS 3 Minimum	41	9" x 12" x 25"	812FPSA-63M-1-102
	CAR Minimum	41	9" x 12" x 25"	812FPSA-6CM-1-102
	Part 29/91/135/EU OPS1/3 & CAR Universal Min	45	9" x 12" x 25"	812FPSA-6UM-1-102

Toll Free: (800) 838-3012 ~ Fax (941) 613-6677
www.winslowliferaft.com ~ rafts@winslowliferaft.com

